


# Linea Dary

**MODEL:** LINEA DARY BLACK REFLECTOR/ PENDANT/SURFACE /1125mm  
/ 24W / 3500lm / 4000K / IP40 / UGR<19/CRI>80 /BLACK BODY  
**CODE:** LINEA DARY B-P/S 50x1125-24- 3500/9.4/IP40B  
**LED LIGHT SOURCE**

*Mareli Ltd*  
www.mareli-bg.com

## STANDARD



## SPECIFICATIONS

<b>Mounting</b>	Suspended
<b>Light source</b>	LED
<b>Optical system</b>	Lenes and Reflector
<b>Materials</b>	Housing: Extruded Aluminum Profile Lenses: 8N PMMA Reflector: Polycarbonate
<b>Wiring</b>	ECG
<b>Light Distribution</b>	Direct
<b>Connection</b>	3-pole
<b>Surface finish</b>	RAL 9005; Black
<b>Protection class IEC</b>	Safety class I
<b>Input Voltage, Frequency</b>	220-240 V / 50 to 60 Hz
<b>Power Factor (Min)</b>	0.9
<b>Ambient Temperature</b>	-5 to +45 °C
<b>Photobiological safety class</b>	Exempt group



<b>Luminaire luminous flux</b>	3500 lm
<b>Luminaire efficacy</b>	146 lm/W
<b>EN 60598</b>	Compliant
<b>Beam angle</b>	80°
<b>Corr. Color Temperature</b>	4000K
<b>Color Rendering Index</b>	≥80 Ra
<b>Rated median useful life</b>	L80B20 at 50 000 hours
<b>Ingress protection</b>	IP40
<b>Impact protection</b>	IK07
<b>UGR</b>	<19
<b>Accessories</b>	Black Optic Set of Single Suspenders 2 m long
<b>Warranty</b>	5 years

## Recommended Areas of application



## LINEA DARY B-P/S 50x1125-24- 3500/9.4/IP40B

<b>Linea Dary</b>	Name of series
<b>B-P/S</b>	Suspended, Surface
<b>1125x50x72</b>	Dimension: 1125x50x72
<b>24</b>	Power (W)
<b>3500</b>	Net lumen output
<b>9.4</b>	4000K
<b>IP40</b>	Ingress protection
<b>Black reflector</b>	Dary OpticB



Light Distribution Graph

CODE	OPTICAL SYSTEM	POWER	LIGHT SOURCE	NET LUMEN OUTPUT	DIMENSION	COLOR RENDERING INDEX	COLOR TEMPERATURE
	Lenes and Reflector	(W)		(lm)	(mm)	(Ra)	(K)
LINEA DARY B-P/S 50x1125-24- 3500/9.4/IP40B	+	24	LED	3500	W H L 50 75 1125	>80	4000